



Nexreg Compliance Inc.
1673 Richmond Street - Suite 501
London, ON - N6G 2N3 - CANADA
Ph: (519) 488-5126
F: (519) 488-5217

Arbeitsmuster von Nexreg Compliance Inc. Sind Beispiele für Dienstleistungen, welche angeboten werden. Nexreg versteht, dass Ihre Produkte einzigartig sind. Unseres Software zur MSDS urheberrechtlichen Überprüfung ist sehr flexibel und kann daher Ihren Bedarf an einer MSDS - Vorbereitung decken. Die Elemente von dem angefügten Muster können editiert werden, um Ihre Präferenzen widerzuspiegeln, inklusive der Gestaltung von Schablonen, der Sprache, Information und mehr.

Warum sollte man die Überprüfung zur gesetzlichen Übereinstimmung von Chemikalien outsourcen?

Nexreg Compliance Inc. ist ein führendes Unternehmen bei der Bereitstellung von gesetzlicher Übereinstimmung der Regulierungen von chemischen Produkten und unterhält ein hingebungsvolles Team, welches die Veränderungen in staatlichen Richtlinien verfolgt; Eine Empagio Studie über die Geschäftsführung von Unternehmen stellte drei wesentlichen Gründe, warum die Unternehmen das Outsourcing durchführen. Nexreg bietet alle drei:

1. **ERHÖHTE LEISTUNGSFÄHIGKEIT** - Bei einer Auftragserteilung an das Nexreg Team kann Ihr Unternehmen diesen für mehr missionskritische Aufgabenstellung einsetzen.
2. **ZEITERSPRANISS** - Nexregs Team zur Prüfung von gesetzlicher Übereinstimmung kann bedeutend die Bearbeitungszeiten reduzieren. Dadurch können Ihre Produkte den Markt schneller erreichen.
3. **KOSTENERSPRANISS** - Das Nexreg Team kann Ihrem Unternehmen an 50-65% für eine Regulierung aufzubringende Kosten ersparen.

Nexreg bietet eine Anzahl von Regulierungsdienstleistungen zu gesetzlichen Übereinstimmung von Produkten, wie z. B. :

- MSDS Urheberrechtliche Überprüfung für eine breite Palette von Zuständigkeitsbereichen
- Übereinstimmung von Produktmarken gemäß der gesetzlichen Anforderung für die Verbraucher-, Kosmetikprodukt- und Industriemärkte
- Beratung über Regulierungen
- Staatliche Einreichungen und Kontrollen von Produktbeschreibungen
- Technische Übersetzungen

Bitte wenden Sie sich an uns, um mehr Informationen über diese Dienstleistungen, Preise und Antworten auf alle Fragen zu erhalten.

Internetseite: <http://www.nexreg.com>
Email: info@nexreg.com
Telefonnummer: Nexreg US: +1 206 418 6663 (Seattle, WA)
Nexreg Kanada: +1 519 488 5126 (London, ON)
Nexreg VK: +44 20 7993 5893 (London, VK)

MATERIAL SAFETY DATA SHEET

Super-Lube

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Super-Lube
Product Number: 90651
Product Use: Lubricant.
Manufacturer/Supplier: USA Lubricants, Inc.
1100 Industrial Avenue
Vernon Hills, Illinois 60061, USA
Phone Number: (800) 857-4544
Emergency Phone: CHEMTREC (800) 424-9300
Date of Preparation: October 24, 2006

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.

Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract and respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	60 - 100

MATERIAL SAFETY DATA SHEET

Super-Lube

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: Oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: This material is a water pollutant. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Vacuum or sweep material and place in a disposal container. Allow gas to dissipate harmlessly into the atmosphere.

Other Information: Not available.

MATERIAL SAFETY DATA SHEET

Super-Lube

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed. Keep away from food, drink and animal feedingstuffs.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Distillates (petroleum), hydrotreated light naphthenic	5 mg/m ³ (mist)	5 mg/m ³ (mist)

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	Colorless.
Odour:	Petroleum odor.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	Not available.
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	~ 149 °C (~ 300.2 °F)
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	> 1 (Air = 1)

MATERIAL SAFETY DATA SHEET

Super-Lube

Specific Gravity: 0.848
Solubility in Water: Negligible.
Coefficient of Water/Oil Distribution: Not available.
Auto-ignition Temperature: Not available.
Percent Volatile, wt. %: Not available.
VOC content, wt. %: Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.
Conditions of Reactivity: Heat. Incompatible materials.
Incompatible Materials: Acids. Oxidizers.
Hazardous Decomposition Products: Oxides of carbon.
Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Distillates (petroleum), hydrotreated light naphthenic	Not available.	Not available.

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.

Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.
Chronic Effects: Not hazardous by WHMIS/OSHA criteria.
Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
Distillates (petroleum), hydrotreated light naphthenic	Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.
Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.
Developmental Effects:

MATERIAL SAFETY DATA SHEET

Super-Lube

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material and its container must be disposed of in a safe way.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D

TDG Classification

Limited Quantity

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient

	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Distillates (petroleum), hydrotreated light naphthenic	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient

	Canada DSL/NDSL	USA TSCA
Distillates (petroleum), hydrotreated light naphthenic	DSL	Yes.

MATERIAL SAFETY DATA SHEET

Super-Lube

NFPA - National Fire Protection Association:

Health - 1 Fire - 1 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: October 24, 2009

Version #: 1.0

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com