



Nexreg Compliance Inc.
1673 Richmond Street - Suite 501
London, ON - N6G 2N3 - CANADA
Ph: (519) 488-5126
F: (519) 488-5217

Las muestras de los servicios de Nexreg Compliance Inc. ilustran los servicios ofrecidos. En Nexreg entendemos que sus productos son únicos. Nuestro programa de autoría de MSDS está diseñado para ser flexible y, por lo tanto, para satisfacer sus necesidades en la preparación de SMDS. Los elementos de la muestra adjunta se pueden editar para reflejar sus preferencias, incluyendo el diseño de plantillas, idioma, información, etc.

¿Por qué tercerizar la conformidad normativa de sus productos químicos?

Nexreg es el líder en la conformidad de productos químicos y mantiene un equipo de investigación dedicado para monitorear cualquier cambio en las regulaciones gubernamentales. También hay otros beneficios adicionales; un estudio de Empagio sobre los ejecutivos determinó las tres razones principales por las que las compañías tercerizan. Nexreg le proporciona las tres:

1. **MAYOR EFICIENCIA:** Al utilizar el grupo de expertos de Nexreg, el personal de su compañía queda disponible para tareas más críticas para su operatoria.
2. **AHORRO DE TIEMPO:** El equipo de cumplimiento normativo de Nexreg puede reducir sensiblemente los tiempos involucrados con el cumplimiento de normativas, permitiendo que los productos de su compañía alcancen más rápidamente nuevos mercados.
3. **AHORRO DE COSTOS:** El equipo de Nexreg puede reducir los costos normativos de su compañía entre un 50% y un 65%.

Nexreg ofrece un número de servicios de conformidad normativa tales como:

- Autoría de MSDS para una variedad de jurisdicciones
- Conformidad normativa del etiquetado para los mercados de consumo, cosméticos e industriales
- Consultoría de normativa
- Presentaciones gubernamentales y revisión del etiquetado
- Traducciones técnicas

Por favor, contáctenos para obtener mayor información sobre estos servicios, cotizaciones o respuestas para cualquiera de sus preguntas.

Website: <http://www.nexreg.com>

E-mail: info@nexreg.com

Teléfono: Nexreg EE.UU. +1 206 418 6663 (Seattle, WA)
Nexreg Canadá: +1 519 488 5126 (London, ON)
Nexreg RU: +44 20 7993 5893 (Londres, RU)



MATERIAL SAFETY DATA SHEET

Super-Lube

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Super-Lube
Product Number: 90651
Product Use: Lubricant.
Manufacturer/Supplier: USA Lubricants, Inc.
1100 Industrial Avenue
Vernon Hills, Illinois 60061
USA
Phone Number: 800-857-4544
Emergency Phone: 800-424-9300 CHEMTREC
Date of Preparation: October 1, 2005

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING:

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation and ingestion.

Eye: May irritate eyes.

Skin: May irritate skin.

Ingestion: May cause stomach distress, nausea or vomiting.

Inhalation: Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness). Aspiration of material into lungs can cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated exposure can cause drying, defatting and dermatitis.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

Target Organs: Not available.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: This product is not expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient(s)	CAS #	Wt. %
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	60 - 100



MATERIAL SAFETY DATA SHEET

Super-Lube

Section 4: FIRST AID MEASURES

- Eye Contact:** Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
- Skin Contact:** After contact with skin, wash immediately with plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, get medical attention.
- Inhalation:** If breathed in, move person into fresh air. If symptoms persist, obtain medical attention. If breathing has stopped, trained personnel should administer CPR immediately.
- Ingestion:** If swallowed, call a Poison Control Centre or doctor immediately. DO NOT induce vomiting. Never give anything by mouth if victim is unconscious, or is convulsing. If swallowed, rinse mouth with water (only if the person is conscious).

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may be delayed.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: Oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: In case of fire and/or explosion do not breathe fumes. Firefighters should wear full protective clothing including self contained breathing apparatus.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate area. Keep unnecessary personnel away.

Environmental Precautions: Prevent entry into waterways, sewers, basements or confined areas.

Methods for Containment: Prevent further leakage or spillage if safe to do so. Use sand, perlite or vermiculite as an absorbent for large spills of this material.

Methods for Clean-Up: Sweep up or gather material and place in appropriate container for disposal.

Other Information: Not available.



MATERIAL SAFETY DATA SHEET

Super-Lube

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with eyes. Avoid contact with skin. Do not swallow. Do not breathe vapor. Use only in a well-ventilated area. Handle and open container with care. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

Storage:

Keep out of the reach of children. Store in a closed container away from incompatible materials. Store in a cool, dry, well-ventilated area. Keep container tightly closed. Keep away from food, drink and animal feedings.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient(s)	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Distillates (petroleum), hydrotreated light naphthenic	5 mg/m ³ (mist)	5 mg/m ³ (mist)

Engineering Controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear safety glasses with side shields.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations:

Handle in accordance with good industrial hygiene and safety practice.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	Colorless.
Odour:	Petroleum odor.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	Not applicable.
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	> 300 °F (> 149 °C)
Evaporation Rate:	Negligible.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Negligible.



MATERIAL SAFETY DATA SHEET

Super-Lube

Vapor Density:	>1 (Air = 1)
Specific Gravity:	0.848
Solubility in Water:	Negligible.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Conditions of Reactivity: No dangerous reaction known under conditions of normal use.

Incompatible Materials: Acids. Oxidizers.

Hazardous Decomposition Products: Oxides of carbon.

Possibility of Hazardous Reactions: Will not occur.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient(s)	LD ₅₀ (oral)	LC ₅₀
Distillates (petroleum), hydrotreated light naphthenic	Not available.	Not available.

Eye: May irritate eyes. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May irritate skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Ingestion: Not a normal route of exposure. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation. Aspiration of material into lungs can cause chemical pneumonitis.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by OSHA criteria.

Carcinogenicity: Not hazardous by OSHA criteria.

Ingredient(s)

Chemical Listed as Carcinogen or Potential Carcinogen *
Not listed.

Distillates (petroleum), hydrotreated light naphthenic

* See Section 15 for more information.

Mutagenicity: Not hazardous by OSHA criteria.

Reproductive Effects: Not hazardous by OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by OSHA criteria.

Embryotoxicity: Not hazardous by OSHA criteria.



MATERIAL SAFETY DATA SHEET

Super-Lube

Respiratory Sensitization: Not hazardous by OSHA criteria.

Skin Sensitization: Not hazardous by OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: This product is not expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material and its container must be disposed of in a safe way. Dispose in accordance with all applicable regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D

Section 15: REGULATORY INFORMATION

Federal Regulations

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient(s)	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Distillates (petroleum), hydrotreated light naphthenic	-	-	-	No.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient(s)	USA TSCA
Distillates (petroleum), hydrotreated light naphthenic	Yes.

NFPA - National Fire Protection Association:

Health - 1 Fire - 1 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme



MATERIAL SAFETY DATA SHEET

Super-Lube

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Version #: 1

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

Web: www.nexreg.ca